

## Techbelt is based in the heart of Yorkshire and is ideally positioned to provide high quality baler belts to the local and wider area farming community.

Our belts are manufactured from high quality material manufactured in the USA and will suit a wide range of baler machines such as Claas, Vicon, Massey Fergusson and Welga. These machines suit our textured top baler belts which have a heavy duty reinforcement construction in 3 ply layers. This is for added strength when continually flexing around rollers.

We can also offer, on special order, belts for John Deere Baler machines which have a diamond texture top like the OEM part and can be supplied in roll form or clipped with a mechanical fastener.

New Holland machines such as the 640 and 650 can be supplied with truly endless belts on special order by request.

When Baler belts are supplied as finished lengths or with a mechanical clipped joint, we tend to use the MATO fastener which is regarded as one of the best in the market.

As baling is seasonal, stocks tend to be much higher in the on season however if you are carrying out baler maintenance in the winter months please contact us with your requirements / size of belts as we would be only too pleased to help.

For ease of payment we have card processing facilities which means you can order your baler belts with confidence knowing payments can be made straight away therefore not holding you up should time be important.

If you have a requirement for replacement belts for your round baler, please contact Techbelt today either by phone on **01422 366386** or use our easy to use contact form for a quick response which is on this page.

Please note all our baler belts are after market products and are not sold as genuine dealer part.




## **ROUND BALER BELT**

After Market Belts for New Holland Round Baler Machines					
Belt Thickness (mm)	5.2	Weight (Kg/ml)	6		
Top Cover Thickness (mm)	1.5	Bottom Cover Thickness (mm)	0.5		
Operating Temperature (°C)	-25 to +80	Maximum Width	1000mm		

Construction Mechanical Properties					
Carcass Type	Plied	Warp Yarns	Polyester		
Number of Plies	3	Tensile Strength	> 315 N/mm		
Elongation at Break Warp	> 10%	Elongation Under 10% Load	< 1.5%		
Adhesion Between Cover & Carcass	> 4 N/mm	Adhesion Between Plies & Plies	> 4.5 N/mm		

Cover Mechanical Properties					
Tensile Strength at Break	> 18 Mpa	Elongation at Break	> 450%		
Abrasion	< 170 mm <sup>3</sup>	Hardness	62		



## **Material Properties**

Techbelt is a manufacturer of aftermarket round baler belts made to fit a wide range of round baler machines available such as New Holland. Our products are not genuine OEM parts and are

aftermarket products which are hand cut and customised to suit your machine. We carry a large amount stock and can dispatch these in 1-2 days from placing your order – Sooner if required. We only use the highest quality materials that in our opinion match the quality of genuine dealer parts. The belts come with a MATO clipper fastener for ease of installation.

## **Additional Information**

Availability: This material as available ex stock and can be supplied at any width up to 1000mm wide.

Techbelt manufactures 3 ply rubber baler belts to suit any type of round baler available on the market today. We can make belts to suit machine such as New Holland, John Deere, Vicon, Claas, Heston, Massey Ferguson, Vermeer and Welger. Ifyour machine isn't mentioned give us a call with the size and we can custom make a baler belt to fit your specific needs.

All our round baler belts are made to order here at our UK facility using the highest quality sourced materials from our trusted manufacturing partners in the EU

Woodside Mill | Halifax Road | Elland HX5 0SH t: 01422 366386 f: 01422 344453 e: sales@techbelt.com